



1



2



## Introduction & Outline



3

3



## Charter Steel Saukville Melting (CSSM)

### Basic information

First heat produced on  
September 13, 1991

2024 Good Tons produced:  
528,191

Operating schedule: 24/7 with  
a scheduled weekly down day  
from 4-12 hours typically

Employees work a 5-2-2-5  
base schedule, 12 hour shifts



4

4





## Charter Steel Cleveland Melting (CSCM)

### Basic information

First heat produced on

June 15, 2006

2024 Good Tons

produced: 507,487

Operating schedule similar  
to Saukville




5

5




## Saukville Melt Shop Layout



6

6


## Process Outline



7

7

## Scrap / Iron Units



8

8





## Arriving Scrap

### By truck and rail

About 85% of our scrap arrives by truck, 15% by rail

All arriving scrap must go through radiation detectors. These are backed up by hand-held units and other redundant systems.

Truck drivers are directed where to dump

Railcars are moved by our own personnel and unloaded by crane



9

9



## Busheling

### Key scrap type

Trimblings from sheet stamping operations, etc.

Busheling is relatively low in metallic residuals (Cu, etc.)

Density low compared to other scrap types



10

10

## Bundles

### Pressed scrap

Some busheling-type scrap gets pressed into bundles

This increases the density and improves handling/yield

CSSM uses 2 foot x 2 foot x 2 foot bundles, typically. They are usually charged in the bucket.



11

11

## Rail Scrap

### Wheels and cut rail

Provide more density to mix

Fairly consistent chemistry



12

12





## Auto Shred

### Recycled cars

Scrap suppliers run stripped, compacted automobiles through shredder that separates ferrous material from others

In spite of separation, some copper wires, etc. remain

Ideal density for a continuously-fed scrap charge, like we have in Saukville



13

13



## Shredded Clips

### Similar to auto shred

Another type of shredded scrap

Old appliances, slitter scrap, etc.

Ideal density for continuous scrap feed



14

14

## Alloy Scrap

### Segregating valuable scrap

Scrap and revert material known to have alloy content

Reduces need for other alloy additions

Typically used for 86XX and similar grades  
(nickel, chromium, and molybdenum ranges)



15

15

## Pig Iron

### “Clean” iron units

Iron from blast furnaces that is poured off into “pigs”

Provides carbon (typically 4%) – foaming aid

Little to no metallic residuals – dilution

Takes extra energy to melt – density

Higher metallic percentage than other “clean” iron units such as hot briquetted iron (HBI)



16

16





## Loading Scrap

### ROS (Remote Operating System)

The scrap crane operator uses the 34-ton scrap crane (primarily) to load scrap in buckets and on the charge conveyor per the scrap recipe

Operator has many camera views as well as the main furnace screen



17

17



## Charge Buckets / Conveyor

### Start of scrap charge

A 60-65,000 lb bucket is prepared to start each heat

Remaining scrap is loaded onto the charge conveyor

Slip/stick style conveyor to move the scrap forward



18

18



## Incline Conveyor

### Through raw material warehouse

The incline (13°) conveyor moves the scrap up and drops it onto the preheat conveyor

Belt-type conveyor



19

19



## Preheat Conveyor

### Preheating the scrap

Slip/stick style conveyor to move the scrap forward

The preheat conveyor uses off-gas from furnace to preheat the scrap to approximately 600°- 800° F

Experimented with air jet turbulators to further mix the gases through the scrap

Hoods/ducts are a combination of refractory-lined and water-cooled to control off-gas temperature



20

20





21

21

## Furnace Process

**Specific energy is key**

Heel (50+ tons) remains in furnace

A smaller amount (7 – 10 tons, typical) is fed from the conveyor into the bath to help control bath temperature and volatility

The roof is opened and the bucket charge is dropped. Roof is closed and arcing begins.

Bucket step / Use of burners, then switching to carbon and HS oxygen

Consteel step / Resume scrap feed while continuing injection

Refining step / Continue injection to refine the heat

22

22



## Powering the Electric Arc Furnace (EAF)

### Electric energy to melt

Saukville site is fed with 138 kV line, stepped down to 26.4 kV (for furnace) at our north substation

The furnace is powered by dual transformer/rectifiers

Operating power is 62 MW (620 V, 100\* kA)

Direct current (DC): single electrode with pin bottom anode (40 pins are thermocoupled so we can monitor)

\*Currently testing 105 kA



23

23



## Top Feed System

### Slag formation

Carbon (anthracite) and dolomitic lime are top fed through the roof of the furnace to build slag and control its composition



24

24





## Inside the Furnace

### Brick, panels, injectors

Bottom of furnace lined with refractory brick

Top of furnace uses water-cooled panels

Injectors angled downward from panels to treat the steel scrap/bath

As natural gas burners

For chemical reactions/energy

Also have one lime injector (hi-cal/dolo)

25



25



## Auto Sampler

### Safe sampling of heat in furnace

Thermocouple probes for temperature (disposed)

Sampler tubes to collect "lollipop" samples to be sent by pneumatic tube to the lab for chemistry

26



26



## Chemistry Testing

### CSSM Lab

Sample ("duckbill") is ground and the thicker part is run on an optical emission spectrometer (OES) for most elements

Photo is staged – door would normally be closed

A 1 gram punching is taken from the thin part to run on a Leco (combustion analysis) machine for nitrogen (these machines also test oxygen when needed)

Chemistry is sent back through the computer system to operators to verify chemistry is acceptable and to calculate alloy additions



27

27



## Ready to Tap

### Reaching the end...

A heat is ready to tap from the furnace when

- The chemistry (somewhat generic) is verified as acceptable

- The free oxygen content of the furnace is above 500 ppm (C ~0.10%)

- The aim tap temperature is achieved (typically 3050° F)

- Ladle is in place, etc.



28

28






## Ladles - Prep

### Ready to tap steel into

Ladles are kept heated to around 1600° F to prevent heat loss and thermal shock to the brick

Nozzles and gates are maintained between heats

When ready, nozzle well is sanded to protect the gate plates



29

29



## Tap Additions...

### ...to the 100 tons in the ladle

Carbon from hopper (as needed)

Alloy from hopper for supersacks of other alloys (as needed)

Bulk alloy bins (ferrosilicon, silicomanganese, ferromanganese, ferrochromium, nickel) and other alloys in bags/drums loaded into car

Furnace gas Eccentric Bottom Tapping (EBT); synthetic slag added from hopper



30

30




## Vacuum Arc Degasser (VAD)



31

31




## Synthetic Slag

**A lot more than dirt/dust**

Argon stirring (using porous plug in the ladle) mixes steel and slag to aid in melting and consistency

The pre-mixed bag of synthetic slag contains hi-cal lime, dolomitic lime, silica sand, and fluorspar (for fluidity) to achieve a targeted ladle slag chemistry

The slag performs several key functions including insulation, sulfur removal, inclusion absorption, and coating the ladle brick



32

32





## VAD Process

### Refining the heat

Additional heating is done due to temperature losses at tap / alloy additions

Chemistry sample to measure bulk addition

Trim chemistry and degas

Chemistry sample to measure trim addition

Boron heats require an in-process exit from the chamber for titanium (cored wire) addition



33

33



## Inside the VAD

### Finkl-Mohr Degasser

Box-type degasser in which the ladle and car move into the chamber

Swing tracks / door

Chamber has two ladle positions: VAD/VOD

Ladle continues to stir with argon

AC electrodes to reheat

Vacuum to < 200 Torr

Safety wall for cleaning/maintenance



34

34



## VAD Auto Alloy Addition System

### Reducing Manual Additions

Four most common trim alloy additions at the VAD are now added with this system:

Carbon, Ferrosilicon, Silicomanganese, Ferrochromium

Weigh hopper loads automatically, sends to surge hopper

Other alloys (typically in 50 lb bags) added through separate surge hopper

35



35



## Exiting the VAD

### Finishing the heat

Final carbon, sulfur, boron wire trim additions

Temperature using the west temp pole

Reduce stir to a gentle "rinse"

When ready, craneman picks up ladle and checks with vision system for hot spots, then proceeds to the caster tower

36



36




**CHARTER  
STEEL**


# Continuous Caster





37

37


**CHARTER  
STEEL**

## Caster Process

### Semi-finished steel


Ladle opened, steel fills tundish

Strands started, speed established

Four-strand billet caster, casting on a 26' radius

Section size: 5.5" x 5.5"

Cut to ~ 44' length



38

38



## Caster Turnaround

### Between casts

After the last cast has finished, operators will clean the molds, dress the dummy bar heads, verify aluminum wire targeting, and set the shrouds.

A new, preheated tundish is brought into place



39

39



## Ladle at Caster

### Preparing to cast

Ladle is set in tower with crane

Hydraulic, argon, air hooked up

Ladle shroud / gasket attached using manipulator



40

40





## Tundish

### Directing steel to the strands

Tundishes sprayed, dried off-line

When ready, tundish is preheated

Ladle stream targeted within center pad to limit turbulence

Cones around nozzles to gain height before opening

Tundish powder added when level reached

Typically cast with ~ 11 tons in tundish

Design has been *extensively* water modeled



41

41



## Tundish to Mold

### Protecting the stream

Bellows-style shrouds between tundish and molds protect the steel stream coming through the metering nozzles

Automatic gates to shut off strand when finished casting



42


42



## Inside the Mold

### Critical point in process

- Mold level control
- Oil lubrication
- Oscillation (hydraulic)
- EMS (dual coil)
- Aluminum wire feed



43

43



## Copper Mold Tube

### Heart of the casting machine

The copper mold tube is a highly engineered part of the caster, critical to product quality

Parameters that have been developed over the years include:

- type of copper
- coating on inside
- taper
- thickness, corner radius
- added machining to adjust cooling

44

44







## Starting the Process


### Dummy bar – not what you think

Dummy bars are run up into the mold and the heads are dressed. They are then set in the mold to needed depth.

At start of cast, steel freezes to dummy bar head and the bar withdraws the strand from the mold.

After passing through the lower part of the caster, the tangent rolls engage and take over the strand withdrawal.

45



45



## Torches

### Cutting the strand

Oxy-acetylene torches cut the crops at the start and end of each cast, as well as the individual billets.

The billets pass through a high-pressure descaler before reaching stops and getting moved onto cooling bed.

46



46




## Cooling Bed

### Keeping things straight

The rakes of the cooling bed move in order to rotate billets 90° each time

Billets continue to cool

Even cooling helps keeps them straight



47

47



## Sequence Casting


### Multiple heats through the same tundish, etc.

CSSM caster does not have a turret; must remove one heat and bring next one in

Tundish must begin to refill before minimum weight is reached

Only like / very similar grades are sequenced to avoid long intermix billets that get scrapped

Carbon  
Storage Bin



48

48



**CHARTER STEEL**

## Billet Handling / Inspection




49

49


**CHARTER STEEL**

## Inside Billet Yard

### Primary Billet Storage

Approximately 20,000 tons of inside billet storage

Billets moved using chains



50

50



## Outside Billet Yard

### Additional Billet Storage

Approximately 30,000 tons of additional billet storage

Billets moved in/out with a transfer car



51

51




## Billet Identification

### Importance of traceability

Billets dropped off of the walking bed are identified with heat number as well as individual strand and billet number. Thus, each billet is uniquely identified (these are linked to coil number when rolled).

The numbers are written with a lumber crayon, and then a bar-coded tag is welded on.

Should any uncertainty arise about the identification of a billet, it gets scrapped.



52

52






## Heat Chemistry

### Certification values

The three samples taken from the tundish are used to provide the certified chemistry for the heat.

As CSSM adds aluminum in the mold, the final aluminum value for the heat must come from samples from the cast.

53



53



## Billet Inspection

### Targeted inspection of surface

Depending upon steel grade, quality level, and the caster quality model, billets are selected for inspection.


Billets are inspected visually for cracks, pinholes, "reox," casting laps, and other anomalies.

Cracks are rejected

Others are ground out by hand

Data also provides some feedback to our process

54



54




## Moving Billets Outside

### Mobile gantry crane

If billets are to be moved outside, they are loaded on a transfer car that travels between the inside and outside billet yards.

A rubber-tired gantry crane then lifts the billets and takes them to the outside storage racks.

55



55



## Loading the Skid Bed

### Start of Rolling

Billet Haulers retrieve billets from yard per rolling schedule and bring them to the skid bed to be charged into the reheat furnace.

56



56





57